



IECEX Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEX Scheme visit www.iecex.com

Certificate No.: **IECEX INE 21.0056X** Page 1 of 3 [Certificate history:](#)
Status: **Current** Issue No: 0
Date of Issue: 2022-02-22
Applicant: **BARTEC F.N. S.R.L.**
Via M. Pagano, 3
I - 20090 Trezzano sul Naviglio (MI)
Italy
Equipment: **Lighting fixtures series GLL-*****
Optional accessory:
Type of Protection: **db, eb, mb, tb**
Marking: Ex db eb mb IIC T5 or T4 Gb
Ex tb IIIC T85°C Db IP66
The complete marking is detailed in Annex.

Approved for issue on behalf of the IECEX
Certification Body:

Position:

Signature:
(for printed version)

Date:
(for printed version)



Thierry HOUÉIX

Ex Certification Officer

2022-02-22

Signé électroniquement
Digitally signed by
Thierry HOUÉIX
Ex Certification Officer
Délégué Certification

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

INERIS
Institut National de l'Environnement Industriel et des Risques
BP n2 / Parc Technologique ALATA
F-60550 Verneuil-en-Halatte
France



controlling risks |
for sustainable development



IECEX Certificate of Conformity

Certificate No.: **IECEX INE 21.0056X**

Page 2 of 3

Date of issue: 2022-02-22

Issue No: 0

Manufacturer: **BARTEC F.N. S.R.L.**
Via M. Pagano, 3
I - 20090 Trezzano sul Naviglio (MI)
Italy

Manufacturing
locations:

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

[IEC 60079-0:2017](#) Explosive atmospheres - Part 0: Equipment - General requirements
Edition:7.0

[IEC 60079-1:2014-06](#) Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"
Edition:7.0

[IEC 60079-18:2017](#) Explosive atmospheres - Part 18: Protection by encapsulation "m"
Edition:4.1

[IEC 60079-31:2013](#) Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
Edition:2

[IEC 60079-7:2017](#) Explosive atmospheres - Part 7: Equipment protection by increased safety "e"
Edition:5.1

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

[FR/INE/ExTR21.0040/00](#)

Quality Assessment Report:

[IT/CES/QAR09.0003/14](#)



IECEX Certificate of Conformity

Certificate No.: **IECEX INE 21.0056X**

Page 3 of 3

Date of issue: 2022-02-22

Issue No: 0

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

The LED lighting fixture series GLL-*** is suitable for gas explosive atmospheres EPL Gb for Group IIC and for dust explosive atmospheres EPL Db for Group IIIC.

The "Ex eb" and "Ex tb" enclosure is realized by a transparent polycarbonate cover and a body made in Glass Reinforced Plastic. Protection degree is obtained by a gasket fitted inside a groove on the body and by closing clips as detailed in the instruction manual. When required as defined in the instruction manual, a venting valve covered by Ex Component Certificate could be fitted on the body. The enclosures are provided with plain entries for cable glands or blanking elements.

The lighting fixture includes :

- One LED module protected by "Ex mb"
- One driver housing protected by "Ex db" closed by an integral sealed bushing on one side.
- Terminals covered by Ex Component Certificates and internal wiring protected by "Ex eb"

The lighting fixture get the degrees of protection IP66 in accordance with IEC 60529.

SPECIFIC CONDITIONS OF USE: YES as shown below:

- Potential electrostatic charging hazard: clean only with a damp cloth. See also the instruction manual of the manufacturer.
- During the installation, the user will take into consideration that the equipment underwent only a shock corresponding to an energy of a low risk.

Specific conditions of use referring to the driver housing model "EB" protected by "Ex db":

- The widths of the flameproof joints are superior than those specified in tables of IEC 60079-1 standard. To contact the original manufacturer for any repairs of the flameproof joints.
- The two covers shall be fixed by screws with minimum quality A2-70.

The instructions for safe use are completed by those stipulated in the instructions manuals of the manufacturer

Annex:

[IECEX INE 21.0056X-00_Annex.pdf](#)



IECEX Certificate of Conformity

Certificate No.: IECEx INE 21.0056X

Issue No.: 0

Page 1 of 2

Annex: IECEx INE 21.0056X-00_Annex.pdf

PARAMETERS RELATING TO THE SAFETY

Maximum Voltage/Frequency: 277 Vac / 50÷60 Hz

Nominal power of LED module: 45 W for lighting fixture GLL-088

The lighting fixture include internal suitable fuse with nominal current of 400 mA and capable to withstand a prospective short-circuit current of 1500 A to protect the "Ex mb" LED modules.

The lighting fixtures can be used in the following ambient temperature range:

- From -20°C to +53°C for temperature class T5 / T85°C
- From -20°C to +60°C for temperature class T4 / T85°C

MARKING

Marking has to be readable and indelible; it has to include the following indications:

- BARTEC FN ⁽¹⁾
- I - 20090 Trezzano sul Naviglio (MI)
- GLL-*** ⁽²⁾
- IECEx INE 21.0056X
- (Serial number)
- Ex db eb mb IIC T⁽³⁾ Gb
- Ex tb IIIC T85°C Db
- IP66
- -20°C < Tamb < ...°C ⁽³⁾
- *Rated Current and Rated Voltage or rated power (as defined in the manufacturer's documents)*
- **WARNINGS:**
 - DO NOT OPEN WHEN AN EXPLOSIVE ATMOSPHERE IS PRESENT
 - DO NOT OPEN WHEN ENERGIZED
 - POTENTIAL ELECTROSTATIC CHARGING HAZARD – SEE INSTRUCTIONS

⁽¹⁾ Optional Brands "BARTEC FEAM" or "BARTEC NASP" can be added in the marking with the sentence "manufactured by BARTEC FN"

⁽²⁾ The dots are replaced by a codification according to the manufacturing variations.

⁽³⁾ Temperature class T5 for ambient temperature up to +53°C
Temperature class T4 for ambient temperature up to +60°C

ROUTINE EXAMINATIONS AND TESTS

- In accordance with clause 7.1 of the IEC 60079-7 standard, each lighting fixture has to have successfully passed; before delivery, a dielectric strength test on each of the different circuits of the connection units, performed according to the relevant standards, the supply voltage shall be applied during one minute.
- In accordance with clause 9.1 from the IEC 60079-18 standard, each LED module shall be subjected to visual inspection after polymerisation of the resin in order to check that there is no damage that could impair the protection mode.
- In accordance with 9.2 of the standard IEC 60079-18, each LED module shall successfully pass a dielectric strength test at the relevant supply voltage between active parts and metallic frame.
- In accordance with clause 16.2 of the IEC 60079-1 standard, the driver housing is exempted of routine test due to the fact that it has undergone a static type test at 4 times the reference pressure under 28.8 bar



IECEX Certificate of Conformity

Certificate No.: IECEx INE 21.0056X

Issue No.: 0

Page 2 of 2

Annex: IECEx INE 21.0056X-00_Annex.pdf

TABLES

TABLE 1 : LIST OF Ex COMPONENTS

| Ex component | Manufacturer | Type | Certificate | Standards | Ex Marking |
|---------------|-----------------------------------|--------------------------------|-------------------------------|--|------------------------------------|
| Venting Valve | W. L. Gore & Associates GmbH | Gore® PolyVent Ex+ (PMF200400) | IECEX IBE 17.0013U (Issue 02) | IEC 60079-0: 2017 IEC 60079-7: 2017 IEC 60079-31: 2013 | Ex eb IIC Gb Ex tb IIIC Db IP66 |
| Terminals | WAGO Kontakttechnik GmbH & Co. KG | 862..... | IECEX PTB 05.0003U (Issue 03) | IEC 60079-0: 2017 IEC 60079-7: 2017 | Ex eb IIC Gb |
| Terminals | Weidmüller Interface GmbH | WDU | IECEX ULD 14.0005U (Issue 07) | IEC 60079-0: 2017 IEC 60079-7: 2017 | Ex eb IIC Gb |
| Terminals | Weidmüller Interface GmbH | AKZ-AKE | IECEX TUR 18.0024U (Issue 02) | IEC 60079-0: 2017 IEC 60079-7: 2017 | Ex eb IIC Gb |